

- Switches with connecting terminals in accordance with VDE 0632.
- Can be illuminated as defined by German workplace regulations of 20.03.1975.
- Notes on materials:
Resistant to aggressive atmospheres due to use of corrosion-resistant metal parts from special alloys and extensively chemical-resistant polyamide housing.

▣ **Material:** Thermoplastic.

▣ **Technical Information:** AGRAR dimensions (⇒ p. 442)

Switches, push-buttons and accessories

▣ **Technical Information:** Circuit diagrams for installation of switches and push-buttons (⇒ p. 427)



Rocker switch

16 AX, AC 250 V

Illuminated.

With screw terminals.

Type of protection: IP 55

IP55

▣ **Accessories:** Neon lamp attachment with integrated lamp, art. no. 396502. Plug-in light attachment E 10, art. no. 396576. Neon lamp E 10, art. no. 395100. LED lamp E 10, art. no. 3951...

Version	Art. no.	PU	PG	Info
two-way, green	370677	1/30	2	



Rocker control switch

16 AX, AC 250 V

Can also be used as a 1-pole, one-way control switch.

With screw terminals.

Type of protection: IP 55

IP55

▣ **Contents:** With neon lamp.

Version	Art. no.	PU	PG	Info
two-way, green	372677	1/30	2	



Rocker button

10 A, 250 V AC

Illuminated.

With plug-in terminals.

Type of protection: IP55

IP55

▣ **Accessories:** Neon lamp attachment with integrated lamp, art. no. 396502. Plug-in light attachment E 10, art. no. 396576. Neon lamp E 10, art. no. 395100. LED lamp E 10, art. no. 3951...

▣ **Contents:** 1 light, 1 door, 1 bell per push-button.

Version	Art. no.	PU	PG	Info
two-way, 1-pole, green	375977	1/30	2	



Symbols, rectangular

For rockers and switches with square opening.

Version	Art. no.	PU	PG	Info
neutral, clear	395569	100/4000	1	
light, clear	395669	100/4000	1	
door, clear	395769	100/4000	1	
bell, clear	395869	100/4000	1	
neutral, red transp.	395900	100/4000	1	



Neon lamp attachment with integrated lamp

AC 230 V, 0.65 mA

For all 1- and 2-pole switch inserts.

For monitoring or lighting.

▣ **Contents:** With neon lamp.

Version	Art. no.	PU	PG	Info
grey	396502	10/1000	1	



Plug-in light attachment E 10

For all 1- and 2-pole switch inserts.

For monitoring or lighting.

Caution!

For low voltage variants (e.g. 8 V) we recommend a display lamp, 24-30 V, tubular, E 10, up to 25 mm in length.

▣ **To be completed with:** Neon lamp E 10, art. no. 395100. LED lamp E 10, art. no. 3951...

▣ **Contents:** Without neon lamp.

Version	Art. no.	PU	PG	Info
	396576	10/1000	1	



LED lamp

AC/DC 230 V, AC/DC 24 V

Suitable for plug-in light attachment E 10 or light signal E 10 insert.

▶ **To be completed with:** Plug-in light attachment E 10, art. no. 396576. Light signal E 10 insert, art. no. 319016.

■ **Note:** Current consumption approx. 20 mA

Version	Art. no.	PU	PG	Info
AC 230 V, red	395120	20/240	1	
AC 230 V, yellow	395121	20/240	1	
AC 230 V, green	395122	20/240	1	
AC 230 V, blue	395123	20/240	1	
AC 230 V, white	395124	20/240	1	
AC 24 V, red	395131	20/240	1	
AC 24 V, yellow	395132	20/240	1	
AC 24 V, green	395133	20/240	1	
AC 24 V, blue	395134	20/240	1	
AC 24 V, white	395135	20/240	1	



Neon lamp E 10

AC 230 V, 0.65 mA

Low current consumption (approx. 0.65 mA) and low starting voltage (max. 120 V) mean it is particularly suitable for stairwell and fluorescent lamp circuits.

▶ **To be completed with:** Plug-in light attachment E 10, art. no. 396576.

Version	Art. no.	PU	PG	Info
AC 230 V, 0.65 mA	395100	20/4080	1	

SCHUKO socket-outlets



SCHUKO socket-outlet

16 A, AC 250 V, DIN 49440

Pins and lid springs are made of stainless steel; contacts and connecting terminals are made of special alloys.

Removable base.

With screw terminals.

IP 44

Version	Art. no.	PU	PG	Info
green	279077	1/30	2	



IP 44

SCHUKO triple socket-outlet

16 A, AC 250 V, DIN 49440

With break-out cable entries on all sides.

Pins and lid springs are made of stainless steel; contacts and connecting terminals are made of special alloys.

The socket-outlets can be replaced with any other products in the AGRAR range.

With screw terminals.

■ **Contents:** 2 cable entries.

Version	Art. no.	PU	PG	Info
green	229377	2/8	2	

Accessories



Double entry

For cables and leads.

Version	Art. no.	PU	PG	Info
black	536061	10/1000	2	



Connecting element

For close arrangement of several devices.

Version	Art. no.	PU	PG	Info
grey	535960	10/1000	2	



Slide with gland

For M20 x 1.5 steel armoured conduit with thread or M20 x 1.5 compression gland.

Version	Art. no.	PU	PG	Info
black	533963	10/180	2	