

- Theft-proof thanks to sealed screw holes.
- Indestructible, even when exposed to open flame, tools and heavy blows.
- 4 mm wall-fixing screws anchor the frames and inserts in the masonry.
- Suitable for size 60 mounting box or mounting box, art. no. 528068 with integrated screw fixings and pointed plug holes.
- Switch inserts with connecting terminals to VDE 0632.
- Can be illuminated as defined by German workplace regulations of 20.03.1975.
- Notes on materials:
Insulating lining, thick-walled, die-cast aluminium metal cover.

▣ **Material:** Real metal surface.

▣ **Technical Information:** ANTI-VANDALISM (⇒ p. 438); ANTI-VANDALISM dimensions (⇒ p. 439)

Switches and push-buttons, without frames

Special extra-resistant range

▣ **Technical Information:** Circuit diagrams for installation of switches and push-buttons (⇒ p. 427)



Rocker switch insert

10 AX, AC 250 V

Illuminated.

▣ **Accessories:** Neon lamp attachment with integrated lamp, art. no. 396502. Plug-in light attachment E 10, art. no. 396576. Neon lamp E 10, art. no. 395100. LED lamp E 10, art. no. 3951...

▣ **Further functions available on request.**

Contents: Without frame.

Version	Art. no.	PU	PG	Info
two-way, matt silver	313640	1/30	1.6	
intermediate, matt silver	313740	1/30	1.6	



Rocker control switch insert

10 AX, AC 250 V

Can also be used as a 1-pole, one-way control switch.

▣ **Contents:** With neon lamp, without frame.

Version	Art. no.	PU	PG	Info
two-way, matt silver	322640	1/30	1.6	



Rocker button insert

10 A, 250 V AC

Illuminated.

▣ **Accessories:** Neon lamp attachment with integrated lamp, art. no. 396502. Plug-in light attachment E 10, art. no. 396576. Neon lamp E 10, art. no. 395100. LED lamp E 10, art. no. 3951...

▣ **Contents:** Without frame.

Version	Art. no.	PU	PG	Info
two-way, 1-pole, matt silver	314040	1/30	1.6	



Neon lamp attachment with integrated lamp

AC 230 V, 0.65 mA

For all 1- and 2-pole switch inserts.
For monitoring or lighting.

▣ **Contents:** With neon lamp.

Version	Art. no.	PU	PG	Info
grey	396502	10/1000	1	



Plug-in light attachment E 10

For all 1- and 2-pole switch inserts.
For monitoring or lighting.

Caution!

For low voltage variants (e.g. 8 V) we recommend a display lamp, 24-30 V, tubular, E 10, up to 25 mm in length.

▣ **To be completed with:** Neon lamp E 10, art. no. 395100. LED lamp E 10, art. no. 3951...

▣ **Contents:** Without neon lamp.

Version	Art. no.	PU	PG	Info
	396576	10/1000	1	



LED lamp

AC/DC 230 V, AC/DC 24 V

Suitable for plug-in light attachment E 10 or light signal E 10 insert.

▣ **To be completed with:** Plug-in light attachment E 10, art. no. 396576. Light signal E 10 insert, art. no. 319016.

▣ **Note:** Current consumption approx. 20 mA

Version	Art. no.	PU	PG	Info
AC 230 V, red	395120	20/240	1	
AC 230 V, yellow	395121	20/240	1	
AC 230 V, green	395122	20/240	1	
AC 230 V, blue	395123	20/240	1	
AC 230 V, white	395124	20/240	1	
AC 24 V, red	395131	20/240	1	
AC 24 V, yellow	395132	20/240	1	
AC 24 V, green	395133	20/240	1	
AC 24 V, blue	395134	20/240	1	
AC 24 V, white	395135	20/240	1	



Neon lamp E 10

AC 230 V, 0.65 mA

Low current consumption (approx. 0.65 mA) and low starting voltage (max. 120 V) mean it is particularly suitable for stairwell and fluorescent lamp circuits.

To be completed with: Plug-in light attachment E 10, art. no. 396576.

Version	Art. no.	PU	PG	Info
AC 230 V, 0.65 mA	395100	20/4080	1	

Roller shutter switches

Special extra-resistant range

Technical Information: Roller shutter switch and push-button (⇒ p. 462)



Momentary/maintained-contact switch insert for roller shutters for cylinder locks

10 A, 250 V AC

Splash-proof.
For standard semi-cylinder locks of 40 mm in length.
Can only be used as a single device.

IP 44

Available as a two-way switch on request.

Contents: Complete device with gasket and frame but without lock.

Version	Art. no.	PU	PG	Info
matt silver	318240	1/21	1.6	



Roller shutter push-button insert for cylinder locks

10 A, 250 V AC

Splash-proof.
For standard semi-cylinder locks of 40 mm in length.
Can only be used as a single device.

IP 44

Contents: Complete device with gasket and frame but without lock.

Version	Art. no.	PU	PG	Info
matt silver	318440	1/21	1.6	

Socket-outlets and accessories

Special extra-resistant range



SCHUKO socket-outlet insert with screw terminals

16 A, AC 250 V, DIN 49440

With screw terminals.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	270840	1/30	1.6	



SCHUKO socket-outlet insert with improved protection against accidental contact

16 A, AC 250 V, DIN 49440

Integrated, improved protection against accidental contact in accordance with VDE 0620 Part 1 (replaces the previous designation "child protection").
With screw terminals.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	270940	1/30	1.6	



Socket-outlet insert with earthing pin and increased protection against accidental contact

16 A, AC 250 V, CEE 7 Standard Sheet V

Integrated, improved protection against accidental contact in accordance with VDE 0620 Part 1 (replaces the previous designation "child protection").
With screw terminals.
With claw and screw fixing.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	280838	1/30	1.6	



Loudspeaker socket-outlet insert

With 2 loudspeaker sockets in accordance with DIN 41529 and central plate.
With screw connections.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	295140	1/30	1.6	



Central plate for antenna socket-outlets

For coaxial antenna socket-outlets in line with DIN 45330, e.g., AEG, Astro, Bosch, Fuba, Hirschmann, Kathrein, Philips, Polytron, Siemens, Wisi, Zehnder etc.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	294640	1/100	1.6	



Audio socket

XLR circular connector 3-pole with solder connection and mechanical lock.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	460840	1/30	1.6	



RJ45 telephone connector insert

With 1-gang CAT 5 RJ45 insert.
For connecting analogue or digital terminals using an 8-pole RJ45 socket.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	465740	1/30	1.6	



Blanking cover

Cover for relay, multiple control relay for roller shutters, buzzer, power booster, KNX binary input, flush-mounted/4x10 etc.

Can be used universally with mechanical machining (drilling, milling etc.)

Without claws, for screw fixing.

Contents: Without frame.

Version	Art. no.	PU	PG	Info
matt silver	392340	1/100	1.6	



Mounting box

With screw fixing for ANTI-VANDALISM inserts and frames.

A dovetail connector guarantees the standard combination clearance of 71 mm. Box front with green, closed protective cover for plaster.

Contents: With 2 fixing screws.

Version	Art. no.	PU	PG	Info
green	528068	10/40	1.6	

KNX

The ANTI-VANDALISM range can be integrated into KNX via the bus coupling inserts art. no. 6711 .. on request.

- The ANTI-VANDALISM cover and the bus coupling insert are supplied as a complete device.

ANTI-VANDALISM frames

Special extra-resistant range



Frame, 1-gang

With sealable fixing holes, frame suitable for use as guide for Ø 6 mm plug.

▣ **Replacement part:** Lead seal, art. no. 390199.

▣ **Contents:** With lead seals.

Version	Art. no.	PU	PG	Info
matt silver	480140	1/100	1.6	



Frame, 2-gang

With sealable fixing holes, frame suitable for use as guide for Ø 6 mm plug.

Only for vertical installation with a distance of 71 mm.

▣ **Replacement part:** Lead seal, art. no. 390199.

▣ **Contents:** With lead seals.

Version	Art. no.	PU	PG	Info
matt silver	480240	1/75	1.6	



Frame, 3-gang

With sealable fixing holes, frame suitable for use as guide for Ø 6 mm plug.

Only for vertical installation with a distance of 71 mm.

▣ **Replacement part:** Lead seal, art. no. 390199.

▣ **Contents:** With lead seals.

Version	Art. no.	PU	PG	Info
matt silver	480340	1/58	1.6	



Lead seals

As spare parts for sealing fixing holes.

▣ **Contents:** 1 PU = 8 lead seals

Version	Art. no.	PU	PG	Info
matt silver	390199	1/600	1.6	