

### Main

Product name	SpaceLYnk
Product or component type	Logic controller

### Complementary

Communication port protocol	BACnet Modbus IP (Internet Protocol) KNX
[Us] rated supply voltage	24 V DC
Power consumption	2 W
LED indicator	Green/Red LED (KNX powered/reset) Green LED (CPU load)
Physical interface	1 x TP-UART2 1 x RS232 1 x RS485 1 x RJ45
Port Ethernet	10BASE-T/100BASE-TX
Integrated connection type	1 x USB 2.0 port
Control type	RESET pushbutton
Connections - terminals	Serial : clamp terminal, 1.5 mm <sup>2</sup> Power supply : clamp terminal, 1.5 mm <sup>2</sup> KNX bus : bus terminal, 2 x 0.8 mm <sup>2</sup>
Mounting support	DIN rail
Height	90 mm
Width	52 mm
Depth	58 mm

### Environment

Ambient air temperature for operation	-5...45 °C
Operating altitude	<= 2000 m
Relative humidity	<= 93 %
IP degree of protection	IP20
Directives	2002/96/EC - WEEE directive
Standards	IEC 60950-1

### Offer Sustainability

Sustainable offer status	Not Green Premium product
Product environmental profile	Available
Product end of life instructions	Available